


BM·VOLVO

DUMPER DR 631



- Articulated steering, 4-wheel drive, built for driving both on and off the road
- 10-ton load capacity
- Big--70°--tip angle
- Rugged axles with differential lock: rear axle incorporates hub reduction
- Roomy, well-insulated cab, tested for impact resistance: truck-type driver's seat
- Big wheels, tight turning circle: never-get-stuck performance

Technical particulars

General

Tare weight	8.6 tons
Payload	10 "
Length	8.25 m (325 in.)
Width	2.5 m (98 1/2 in.)
Body-side height	2 m (78 1/2 in.)
Max. steering angle	45°
Tip angle	70°
Load capacity, struck vol., with tailgate	5.4 cu.m. (7 cu.yd.)

Engine

Diesel type	BM 1113 A
Rating at 2000 r.p.m.	65 h.p. SAE
Max. torque at 1,400 r.p.m.	24.5 kgm (177 ft-lb.)

Hydraulics

Pump:	
Working pressure	140 kg/cm ² (1,980psi)
Capacity at 2000 r.p.m. (engine) ...	110 l/min. (24 1/4 Imp.gpm)

The manufacturers reserve the right to change specifications without prior notice.

Gearbox

10 speeds forward, 2 in reverse	
Speed range forward, gears 1-10 ..	2.8-25.8 k.p.h. (1.7-16 m.p.h.)
Speed range in reverse, low/high ..	3.7/4.7 k.p.h. (3/4 m.p.h.)

Brakes

Mechanical, on front section	755 sq.cm. (117 sq.in.)
Pneumatic/mechanical, on rear section	2,675 sq.cm. (414 sq.in.)

Tyres

Front	18.4-34/14
Rear	16.00-24/16

Electrical

System	Bosch 12 V
Battery capacity	152 Ah
Generator rating	450 W
Starter rating	4 h.p.

Optional equipment

Top-hinged tailgate	
Body liners	



BOLINDER-MUNKTELL

a member of the Volvo Group, Eskilstuna, Sweden.